

Vista KM III



SKU	KM-8USB-III
Produkt Verfügbarkeit	
User	1
Ports	4
HE/U	1
DVI	
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	
IP-Zugriff	
Verkabelung CatX/Koax	CatX
Connection PS2/USB	USB
Audio	ja
Access	
Verkabelung CatX/LWL	
Multi Video	

- Switch of USB keyboard and mouse, USB 2.0 devices, and audio (4-port model only) between four or eight computers
- Switch using mouse, keyboard hotkey commands, front panel buttons, or RS-232 serial commands
- Seamless switching feature using mouse does automatic switching when the mouse cursor reaches a display edge
- Can be configured for single-head or multi-head computers
- USB 2.0 devices can be switched independently of keyboard and mouse
- With multiple-head configurations, double clicking the mouse wheel followed by moving the mouse in the direction of an adjacent computer causes switching
- Plug-and-Play installation requires no special drivers and minimal configuration

SPECIFICATIONS

Dimensions

(W x D x H) 12.6" x 6.6" x 1.75" (320 x 168 x 44.45 mm) (1U)

Weight 10 lb (4.5 kg)

Power 100-240 VAC 50-60Hz External adapter, +5V, 2.0A 10W

Distance CPU/KVM: 10 feet (3.0m)

Connectors USB 2.0 host: USB Type B Keyboard: USB Type A Mouse: USB Type A USB 2.0 device: Two USB Type A RS232: DB9 serial port Audio: 3.5mm Female audio jack (4-port only) Power: Barrel jack

Controls	Computer selection: Front panel, hot-key, RS232 or Hot-Mouse Power On: Green LED CPU select: LCD front panel display
Environment	Operating temperature: 32°F-131°F (0°C-55°C) Storage temperature: -4°F-185°F (-20°C-85°C) Relative humidity: 5%-95%, non-condensing