

Vista LC DVI



SKU	KVM-12TDVI-K1
Produkt Verfügbarkeit	
User	1
Ports	4
HE/U	1
DVI	ja
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	
IP-Zugriff	
Verkabelung CatX/Koax	CatX
Connection PS2/USB	USB
Audio	ja
Access	
Verkabelung CatX/LWL	CatX
Multi Video	

- Easy to use, fully featured 12-port digital KVM switch in a 1U chassis
- Handles all DVI video resolutions up to 1920×1200
- The local console port supports DVI-D video, USB-HID keyboard and mouse, and stereo analog speakers
- Each CPU port has a DVI-D connector and a USB B-Type connector that supports keyboard, mouse, and audio signals
- The product kit includes six CPU combo cables (6ft, 2.0m length)
- Supports VESA DDC2B emulation & TMDS signal pass-through
- Switching control is operated by keyboard hotkeys or front panel push-buttons
- Front panel LED's indicate connected CPU ports and the current active channel
- Can be integrated into several models of Rose RackView KVM Drawer products

SPECIFICATIONS

Dimensions

(W x D x H) 17.4" x 6.7" x 1.73" (443 x 171 x 44 mm) (1U)

Weight	5.5 lb (2.5 kg)
Power	100-240 VAC 50-60HzExternal adapter, +12V12W
Resolution	Single-link DVI: 1920 x 1200
Distance	CPU/KVM: 10 feet (3.0m)
Connectors	Video: DVI femaleKeyboard: USB Type AMouse: USB Type AAudio: 3.5mm outputAudio Input: combined with cablePower: Barrel jack

Controls	Computer selection: Front panel or hot-key CPU select: Push-button per port CPU select: Green LED, active link CPU status: Blue LED - connected PC
Environment	Operating temperature: 32°F-132°F (0°C-55°C) Storage temperature: -4°F-140°F (-20°C-60°C) Relative humidity: 5%-90%, non-condensing