

CrystalLink USB1.1 CATx



SKU	CLK-1U1TP-40M
Produkt Verfügbarkeit	
User	1
Ports	1
HE/U	
DVI	
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	
IP-Zugriff	
Verkabelung CatX/Koax	CatX
Connection PS2/USB	USB
Audio	ja
Access	
Verkabelung CatX/LWL	CatX
Multi Video	

- Extends full-speed USB 1.1 up to 130 feet (40 meters) over CATx cable
- Can extend low speed USB HID devices such as keyboard and mouse up to 275 feet (84 meters)
- Will also extend USB 2.0 devices, but at USB 1.1 speeds
- Supports full speed (12Mbps) or low speed (1.5Mbps) USB devices
- Transmitter unit powered by computer USB, Receiver unit powered by Transmitter unit
- Plug and play, no software drivers required
- Supports all major Operating Systems: Windows, Mac OS X, Linux
- Receiver Unit supplies up to 400mA power to USB devices
- Connect up to three self-powered USB hubs to the Receiver to support more USB devices
- Robust ESD and EFT immunity for industrial environments

SPECIFICATIONS

Dimensions (W x D x H)	1.57" x 3.34" x 0.98" (40 x 85 x 25 mm)
Weight	1.35 lb (0.62 kg)
Power	Transmitter: USB poweredReceiver: powered from TX unitUSB Device: receives 400mA when the TX unit is supplied with 600mA
USB Host Support	EHCI (USB 2.0) and OHCI/UHCI (USB 1.1)
Distance	130' (40m)
Connectors	Transmitter:USB host: USB Type ALink: RJ45Receiver:USB device: USB Type A(F)Link: RJ45
Environment	Operating temperature: 32°F-122°F (0°C-50°C)Storage temperature: -4°F-158°F (-20°C-70°C) Relative humidity: 20%-80%, non-condensing