

## CrystalLink USB1.1 CATx Dual Port



|                              |               |
|------------------------------|---------------|
| <b>SKU</b>                   | CLK-2U1TP-40M |
| <b>Produkt Verfügbarkeit</b> |               |
| <b>User</b>                  | 1             |
| <b>Ports</b>                 | 2             |
| <b>HE/U</b>                  |               |
| <b>DVI</b>                   |               |
| <b>VGA</b>                   |               |
| <b>Breite/width</b>          |               |
| <b>Länge/length</b>          |               |
| <b>Multiplattformfähig</b>   |               |
| <b>IP-Zugriff</b>            |               |
| <b>Verkabelung CatX/Koax</b> |               |
| <b>Connection PS2/USB</b>    | USB           |
| <b>Audio</b>                 | ja            |
| <b>Access</b>                |               |
| <b>Verkabelung CatX/LWL</b>  |               |
| <b>Multi Video</b>           |               |

- Extends two USB2.0 devices at USB1.1 speeds
- Supports full-speed (12Mbps) or low-speed (1.5Mbps) USB devices
- Interface powered Transmitter Unit, and self-powered Receiver Unit
- Plug and Play. No software drivers required
- Supports all major Operating Systems: Windows, MAC OS X, Linux
- Remote extender provides up to 400mA power to attached USB devices
- Robust ESD and EFT immunity for industrial environments

### SPECIFICATIONS

#### Dimensions

(W x D x H) 2.17" x 3.34" x 0.87" (55 x 85 x 22 mm)

Weight 1 lb (0.5 kg)

Power Transmitter: USB powered Receiver: powered from TX unit USB, Device: receives 400mA when the TX unit is supplied with 800mA

USB Host Support XHCI (USB 3.0), EHCI (USB 2.0) and OHCI/UHCI (USB 1.1)

Distance 130' (40m)

Connectors Transmitter:USB host: USB Type A Link: RJ45 Receiver:USB device: (2) USB Type A(F) Link: RJ45

Environment      Operating temperature: 32°F-122°F (0°C-50°C) Storage temperature: -4°F-158°F (-20°C-70°C),  
Relative humidity: 20%-80%, non-condensing