

CrystalLink USB2.0 CATx Dual Port



SKU	CLK-2U2TPB-100M/FP
Produkt Verfügbarkeit	
User	1
Ports	2
HE/U	
DVI	
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	ja
IP-Zugriff	
Verkabelung CatX/Koax	
Connection PS2/USB	USB
Audio	ja
Access	
Verkabelung CatX/LWL	CatX
Multi Video	

- Uses standard solid core CATx cable, CAT5e or better
- Supports high-speed (480Mbps), full-speed (12Mbps), and low-speed (1.5Mbps)
- Plug and play, no software drivers required
- Supports all major Operating Systems: Windows®, MAC OS X®, Linux®
- Remote extender provides up to 500mA power to each attached USB device
- Attach up to 4 powered USB hubs for additional remote USB device support
- Rackmountable steel chassis

SPECIFICATIONS

Dimensions (W x D x H)	3.94" x 2.99" x 1.02" (100 x 76 x 26 mm)
Weight	2.2 lb (1 kg)
Power	100-240 VAC 50-60HzOne external adapter, +24V DC, 1A24W
USB Host Support	EHCI (USB 2.0) and OHCI/UHCI (USB 1.1)
Distance	330' (100m)
Connectors	Transmitter:USB host: USB Type BLink: RJ45Power: Barrel jack (24VDC)Receiver:USB device: Two Type ALink: RJ45Power: from TX unit
Controls	Transmitter Unit power: Blue LEDLink status: Green LEDHost status: Green LEDActivity: Amber LEDReceiver Unit power: Blue LEDLink status: Green LEDHost status: Green LEDActivity: Amber LEDUSB Device: Green LED (On), Orange LED (Overpower)
Environment	Operating temperature: 32°F-122°F (0°C-50°C)Storage temperature: -4°F-158°F (-20°C-70°C)Relative humidity: 20%-80%, non-condensing