

CrystalLink USB-3-2-1 CATx



SKU	CLK-4U321TP-100M
Produkt Verfügbarkeit	
User	1
Ports	2
HE/U	
DVI	
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	ja
IP-Zugriff	
Verkabelung CatX/Koax	
Connection PS2/USB	USB
Audio	ja
Access	
Verkabelung CatX/LWL	CatX
Multi Video	

- Locate USB devices where they are convenient to the user or to secure the USB host from unwanted access
- Extends USB 1.1, USB2.0 and USB3.1 devices beyond the standard 3m cable limit, point-to-point connection, up to 330ft (100m)
- Supports all USB1.1, USB2.0, and USB3.1 Gen 1 devices simultaneously at full 5Gbps bandwidth
- Four USB-A Gen 1 ports on the receiver unit, each with 1.5A power, expandable to 30 ports with the use of USB hubs
- One 100/1000 Ethernet channel for transparently extending your network
- Optimum performance with CAT6a and CAT7 (solid core) UTP/STP cabling
- Plug-and-Play installation, no configuration, driver installation, or set-up required
- Supports all major operating systems: Windows, Mac OS X, and Linux
- Transmitter and Receiver units require a +24VDC power adapter (included)

SPECIFICATIONS

Dimensions (W x D x H)	9.1" x 5.4" x 1.3" (232 x 137 x 33 mm)
Weight	5 lb (2.3 kg)
Power	100-240 VAC 50-60Hz24V Model: 24V DC, 1A, Locking, 2.5 mm, center-positive10W
Distance	CAT 6a/CAT 7 solid core:Up to 330' (100m)
Connectors	Transmitter:1× USB3.1 type B connector1× RJ45 Ethernet 100/1000 port1× Ethernet RJ45 link port1× 24V locking power connector1× Mini USB config portReceiver:4 × USB3.1 type A connectors1 × RJ45 Ethernet 100/1000 port1 × Ethernet RJ45 link port1 × 24V locking power connector1× Mini USB config port
Controls	Power, status, link, USB2, USB3

Environment Operating temperature: 32°F–113°F (0°C–45°C) Storage temperature: -4°F–158°F (-20°C–70°C)
Relative humidity: 20%–80%, non-condensing