

CrystalView HDT



SKU

Kits (transmitter, receiver, and power supply) CRK-2HDTXU

Produkt Verfügbarkeit

User

Ports

HE/U

DVI

VGA

Breite/width

Länge/length

Multiplattformfähig

IP-Zugriff

Verkabelung CatX/Koax

Connection PS2/USB

Audio

Access

Verkabelung CatX/LWL

Multi Video

- Transmits 1080p HDMI video up to 330 feet (100m)
- Accepts VGA input up to 1920 x 1200
- Converts VGA and analog audio to HDMI
- Extension over standard CATx cable
- Receivers powered via CATx cable (PoC)
- USB keyboard/mouse and HID touchscreen support
- Dolby TrueHD and DTS-HD audio pass-through
- 1U chassis can house up to 6 HDMI or VGA transmitter cards
- Any combination of HDMI and VGA cards possible, each with local HDMI output
- Monitor hot plug detection and DDC support
- Infrared remote controller support (30 to 56kHz)
- AC and DC redundant power supplies
- Headphone output at receivers for monitoring
- HDMI input is HDCP 1.3 compliant
- Laptop computers can be connected at remote receivers for keyboard and mouse control
- Connected computers can be started via Wake-on-LAN network messages
- Rack mountable options

SPECIFICATIONS

Dimensions Transmitter (6-port): 17.28" x 9.63" x 1.75" (439 x 244 x 44 mm) 1Transmitter (single port): 5.71" x
 (W x D x H) 4.06" x 1.22" (145 x 103 x 31 mm)Receiver (single port): 5.71" x 4.06" x 1.22" (145 x 103 x 31 mm)

Weight	Transmitter (6-port): 6.46 lb (2.93 kg) Transmitter (single port): 0.6 lb (0.27 kg) Receiver (single port): 0.6 lb (0.27 kg)
Power	100-240 VAC 50-60Hz or 48VDC/3.3A Transmitter Chassis: external adapter or POC Single Transmitter: external adapter Receiver: external adapter or POC option when used with POC Transmitter Transmitter (6-port): 160W Transmitter (single port): 10W Receiver (single port): 10W
Resolution	VGA input: 1920 x 1200@60Hz HDMI input: 1080p (50/60Hz) HDMI output: 1080p (50/60Hz)
Audio	Audio pass-through: Surround sound (7.1ch), Dolby True HD and DTS-HD
Distance	HDMI: 330' (100m)
Connectors	Transmitter Cards: HDMI card input video: HDMI female VGA card input video: HD15 (Video/Audio) HDMI local video out: HDMI female USB host: USB Type B Link: RJ45 Power: barrel jack or POC Transmitter Unit: HDMI video: HDMI female HDMI local video out: HDMI female USB host: USB Type B Link: RJ45 Power: barrel jack Receiver Unit: HDMI video: HDMI female USB device: USB Type A (2) Laptop connector: USB Type B
Environment	Operating temperature: 32°F-104°F (0°C-40°C) Storage temperature: 14°F-122°F (-10°C-50°C) Relative humidity: 20%-90%, non-condensing