

CrystalView HDMI 4K60



SKU	CrystalView HDMI 4K60
Produkt Verfügbarkeit	
User	
Ports	
HE/U	
DVI	
VGA	
Breite/width	
Länge/length	
Multiplattformfähig	
IP-Zugriff	
Verkabelung CatX/Koax	
Connection PS2/USB	
Audio	
Access	
Verkabelung CatX/LWL	
Multi Video	

- HDMI 2.0a compliant with HDCP 2.2
- Supports 4K2K@60Hz (4:4:4, 8 bits) and HDR-4K2K@60Hz (4:2:0, 10 bits)
- Extends and HDMI signal up to 330ft (100 meters) at Full HD 1080p, 48-bit and up to 265ft (80 meters) at HDR-4K2K@60Hz
- Supports Power-over-Cable (PoC) so that both the TX and RX units are powered from a single source.
- Supports full-duplex serial RS-232 control up to 115,200bps through a terminal block connector
- Supports full frequency, bi-directional IR signaling and IR pass-through from 20KHz to 60KHz
- Supports uncompressed HDMI 7.1ch digital audio, DTS-HD Master Audio and Dolby TrueHD high-bit rate audio
- Video latency less than 20ms
- HDMI-CEC support
- DIP switch for firmware updates
- Wall or desk mounting design for quick and easy installation
- Packaged with IR transmitter, IR, receiver, and one power supply

SPECIFICATIONS

Dimensions

4.7" x 2.9" x 0.8" (120 x 74 x 20 mm)
(W x D x H)

Weight 0.4 lb (0.12 kg)

Power 100-240V, 50/60Hz External adapter, 12V/2A PoC from TX or RX end using 12V PSU10W

Resolution 4K2K@60Hz (4:2:0, 10 bits), 384MHz 4K2K @60Hz (4:4:4, 8 bits), 594MHz 1080p@60Hz to 330ft (100m) All 3D video formats, x.v. color

Distance	330' (100m)
Connectors	Transmitter:1 x HDMI (In)1 x 3.5mm, IR-TX1 x 3.5mm, IR-RX1 x RJ45, 8P8C (Out)1 x RS-232 (In/Out) Receiver:1 x HDMI (Out)1 x 3.5mm, IR-TX1 x 3.5mm, IR-RX1 x RJ45 8P8C (In)1 x RS-232 (In/Out)
Controls	Power, Link and Signal on front panel
Environment	Operating temperature: 32°F-104°F (0°C-40°C)Storage temperature: -4°F-140°F (-20°C-60°C) Relative humidity: 20%-90%, non-condensing