

UltraVista 4K60



SKU UltraVista 4K60
Produkt Verfügbarkeit
User
Ports
HE/U
DVI
VGA
Breite/width
Länge/length
Multiplattformfähig
IP-Zugriff
Verkabelung CatX/Koax
Connection PS2/USB
Audio
Access
Verkabelung CatX/LWL
Multi Video

- Output resolution between 640x480 to 1920x1200 in 2x2 format
- Input resolution HDMI 4K2K@60Hz (YUV 4:4:4)
- Each DVI/HDMI output has an independent controllable display area
- Resize, position and zoom the video output
- Stereo audio output is provided
- Learns EDID from the default resolution table or from direct connection
- Controller software is included, and software management is via either the USB or Ethernet ports
- Image parameters and layouts can be saved in flash memory and recalled for later use
- Supports IR remote control and is HDCP compliant

SPECIFICATIONS

Dimensions (W x D x H)	11.3" x 7" x 1.7" (288 x 180 x 42 mm) (1U)
Weight	3.3 lb (1.5 kg)
Power	100-240 VAC 50-60HzExternal adapter, +12V DC, 2.0ADVI/HDMI: 12W
Resolution	Input: Up to 4K2K@60Hz (4:2:0 10 bits)Up to 4K2K@60Hz (4:4:4 8 bits)Output: 1920x1080 @60Hz, 1920x1200 @60HzVideo Bandwidth Input: Single link 600MHz (18Gbps)Video Bandwidth Output - DVI (Single-link 4.95Gbps - HDMI (2.25G to 6.75Gbps)
Distance	Video: 25 feet (7.6m)
Connectors	Video in: HDMIVideo out: Four DVIPower: Barrel jackConfig: RS232 DB9, RJ45 Ethernet
Controls	Status LED: Power control on front panel

Environment Operating temperature: 32°F-104°F (0°C-40°C) Storage temperature: -4°F-140°F (-20°C-60°C)
Relative humidity: 20%-90%, non-condensing