

VideoSplitter HDMI 4K60



SKU

VideoSplitter HDMI 4K60

- Distributes a single HDMI video signal to multiple displays
- Three models with either 2, 4, or 8 HDMI outputs
- HDMI 2.0a compliant
- HDCP 2.2 and 1.4 compliant
- Video capability 4K2K@60 4:4:4 8bits and HDR 4K2K@60 4:2:0 10bit
- Video bandwidth: 18Gbps
- Video supports all 3D modes, xvYCC, x.v.Color, and Deep Color
- Audio support includes Dolby Digital, DTS-HD, and Dolby TrueHD audio
- Rotary dial to setup built-in EDID or EDID learning from display
- Mini-USB connector to update firmware
- Cascading feature to increase number of output displays
- Built-in surface mounting bracket

SPECIFICATIONS

Dimensions	8-port: 9.6" x 3.9" x 1" (243 x 98 x 25 mm)4-port: 6.1" x 3.3" x 1" (154 x 83 x 25 mm)2-port: 4.4" x 2.5" x 1" (113 x 62.5 x 25 mm)
Weight	8-port: 0.4 lb (0.88 kg)4-port: 0.3 lb (0.583 kg)2-port: 0.2 lb (0.463 kg)
Power	90-240 VAC 50-60HzExternal adapter, +5VDC8-port/4-port: 4A2-port: 2A8-port: 20W4-port: 15W2-port: 10W
Resolution	HDMI 2.0a compliantHDMI: 3840x2160: 24-bit RGB 4:4:4HDMI: 3840x2160: 36-bit YCbCr 4:2:0
Distance	Video: 10 feet (3m)
Connectors	Video Input: HDMI Type A femaleVideo Output: 2, 4, or 8 HDMI Type A FemalePower: Screw-in barrel jack
Controls	Power: Red LEDVideo ready: Green LEDRotary Dial: EDID mode
Environment	Operating temperature: 32°F-104°F (0°C-40°C)Storage temperature: -4°F-140°F (-20°C-60°C)Relative humidity: 20%-90%, non-condensing