

VideoSplitter HDMI PT



SKU

VS-1x2HDMI-4K/PT

- Connect two HDMI monitors, projectors or LCD displays to a single HDMI video source
- Powered from the HDMI signal
- Ideal for classrooms, boardrooms, trade shows, exhibition displays, and retail advertising or display
- Supports 16:10 computer resolutions to 1920×1200@60Hz, and 16:9 video resolutions to 3840×2160@30Hz
- Video bandwidth to 340MHz per channel for a combined data rate of 10.2Gbps
- Supports 36-bit Deep Color and 3D video
- Supports HD multichannel uncompressed audio
- HDCP 1.4/2.2 compliant
- Built- in input cable eliminates need for extra cable
- Link LED's for input and output video
- Gold plated HDMI connectors

SPECIFICATIONS

Dimensions	2.48" x 2.12" x 0.7" (83 x 54 x 18 mm)
(W x D x H)	
Weight	1.1 lb (0.5 kg)
Power	90-240 VAC 50-60HzExternal adapter, +5VDC, 2AHDMI 2-port Video Splitter: 8W
Resolution	Progressive HDMI: 480p, 576p, 720p, 1080pInterlaced HDMI: 480i, 576i, 1080iComputer resolution: to 1920 x 1200Video Output: High Speed HDMI 1.3bVideo Bandwidth: 2.25Gbps/225MHzHDCP: 1.0/1.1
Distance	Video: Attached HDMI cable 1.6 feet (0.5m)HDMI transmission: 45feet (15 m)
Connectors	Video: Output HDMI Type A(F)Video: Input HDMI Type A(M)Power: Barrel jack
Controls	Unit power: Green LEDVideo active: Green LED per port
Environment	Operating temperature: 32°F-158°F (0°C-70°C)Storage temperature: 14°F-176°F (-10°C-80°C) Relative humidity: 5%-90%, non-condensing